

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)
Temporary Tattoo and Body Makeup (Quick Dry)

Section I

Manufacturer's name

Paasche Airbrush CO

Address (Number, Street, City, State and ZIP Code)

4311 N Normandy Ave

Chicago, IL 60634

Emergency Telephone Number

(773) 867-9191

Telephone Number for Information

(800) 621-1907

Date Prepared

07/26/2012

Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

There are no ingredients present which, within the current knowledge of the supplier and in the concentration applicable, are classified as hazardous to health or the environment and require reporting in this section.

Section II B— Non Hazardous Ingredients:

Zinc Stearate

Ethycellulose

Kaolin

Refined Pharmaceutical Glaze

Alcohol SDA 40-B

Castor Seed Oil

FD&C Pigments, Iron Oxide and Titanium Dioxide

Boiling Point

180(F)

Specific Gravity (H₂O = 1)

.79

Vapor Pressure (mm Hg)

44

Melting Point

242(F)

Vapor Density (AIR = 1)

2.1

Evaporation Rate (Butyl Acetate = 1)

1.4

Solubility in Water Negligible

Appearance and Odor High viscosity liquid of various colors

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) 153(F) -TOC

Flammable Limits

LEL 2

UEL 12

Extinguishing Media Use water fog, alcohol foam, dry chemical, or CO2

Special Fire Fighting Procedures NA

Unusual Fire and Explosion Hazards NA

Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable X		Heat, sparks, flame, & strong oxidizing agents

Incompatibility (*Materials to Avoid*)

Hazardous Decomposition or Byproducts Carbon monoxide and unidentified compounds may occur during combustion

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur X		Store in glass or approved plastic only

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation? X	Skin? X	Ingestion? X
-------------------	---------------	---------	--------------

Health Hazards (*Acute and Chronic*) May be harmful if swallowed.

Extended exposure to vapor may cause irritation to the eyes, nose, and throat.

No known irritation to the skin when applied in small areas.

Carcinogenicity	NTP? NA	IARC Monographs? NA	OSHA Regulated? NA
-----------------	---------	---------------------	--------------------

Signs and Symptoms of Exposure Although rare, watch for headache and irritation to the eyes, nose, or throat if exposed to fumes for extended periods.

Medical Conditions
Generally Aggravated by Exposure

None reported

Emergency and First Aid Procedures

Eyes: Flush with water for at least 15 minutes while holding eyelids open.

Skin reaction: Remove with alcohol or oil based cosmetic remover.

Inhalation: Remove to fresh air.

Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

Clean up excess with dry cloth. Remove residue with alcohol.

Waste Disposal Method Place in leak-proof container for proper disposal.

Precautions to Be Taken in Handling and Storing Keep material in leak-proof container. Store in a cool area.

Other Precautions If using in an enclosed environment for an extended period of time, a mask is recommended.

Section VII—Control MeasuresRespiratory Protection (*Specify Type*)

Ventilation	Local Exhaust X	Special
	Mechanical (<i>General</i>) X	Other

Protective Gloves X Eye Protection NA

Other Protective Clothing or Equipment NA

Work/Hygienic Practices Clean spray and storage equipment regularly.